



la scelta giusta
per grandi progetti.

SCHEDA TECNICA



RM 50

SMOOTH FINISHING MICROEMULSION

PRODUCT

Highly penetrating acrylic microemulsion for masonry, to be applied before coloured and photocatalytic finishing products.

CHARACTERISTICS

Liquid product made from organic polymers in aqueous dispersion at high concentration and workability.

APPLICATION FIELDS

Preparation of the laying substrates for the subsequent application of colored and photocatalytic finishes.

SUBSTRATES

Concrete, cement screeds, plasters and similar.

CONSUMPTION

100 – 150 g/sqm depending on the substrates.

PACKAGING

- 25 kg jerrycans on pallet of 675 kg;
- 5 kg jerrycans on pallet of 600 kg.

STORAGE

It can be stored 12 months in a dry place in its original packaging.

ITEM SPECIFICATIONS

The uneven surfaces before the application of colored and photocatalytic finishes, must be treated with a specific leveling substrate such as RM 50 by Edilcol Italia, applied by brush or roller for 100-150 g / sqm.

PREPARATION

- Make sure that the surfaces to be treated are clean, consistent and dry.
- Stir briefly before of using it.
- Apply the product evenly in a single coat by brush, roller or spray.
- Wait until completely dry before applying any cement-based products.

RECOMMENDATIONS

Do not add water to the product.

Do not apply on non-absorbent surfaces or different ones from those indicated, damp substrates or substrates subject to moisture rising.

Avoid application at temperatures below +5 ° C to +35 ° C.

Protect from frost during storage.

Although the details contained in this product report correspond to the best of our current experience, all the above information must be confirmed after practical applications. Anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of product. The values given in the technical data derived from tests conducted in laboratory , in a controlled environment, so they may be greatly modified by the conditions of installation.

DATI TECNICI

Rev. 02 - 02/2016

Appearance:	Pink liquid	
Composition:	polymer resins in water dispersion and selected additives	
Bulk density:	≈ 1,03 g/cmc	
pH:	≈ 8,0	
Waiting time for heavy coatings:	4 - 5 hours depending on the substrates	
Storage:	12 months in its original packaging, protected from freezing during storage.	
Contribution to smoking:	none	
Hazard classification:	none	(EEC 88/379)