



la scelta giusta
per grandi progetti.

SCHEDA TECNICA



RM 30

PRIMER

PRODUCT

Single-component mineral-based primer for smooth and low-absorbent surfaces before the application of cement adhesives and cement-based finishing products.

CHARACTERISTICS

Viscous yellow liquid product which can be diluted in water made up of the aqueous dispersion of a synthetic copolymer with high stability in an alkaline environment and an inert low density which allows the mixture a good homogeneity over time.

WHERE TO USE

Treatment of smooth surfaces presenting difficulties of adhesion to improve the anchoring of plaster, mortar and cement-based adhesives in class C2.

SUBSTRATES

Screeds, plasters and cement smoothers.

CONSUMPTION

200 – 300 g/m² depending on the substrate.

PACKAGING

- 20 kg buckets on pallets of 600 kg;
- 5 kg buckets on pallet of 650 kg.

STORAGE

RM 30 can be stored 12 months in a dry place in its original packaging and protected from frost.

ITEM SPECIFICATIONS

Before applying to plasters and smoothers, the smooth and not very absorbent surfaces should be treated with an adhesion promoter primer specific such as RM 30 by Edilcol Italia, applied by brush or roller with about 200-300 g/m².



Cert. n. 27935-2008-AQ-ITA

Allianz  RAS

Polizza n. 063294134

PREPARATION

- Mix the primer RM 30 before using it to obtain a homogeneous roughness on the support and effectively improving the anchorage.
- If the product is too viscous in relation to the specific application, dilute it with water to obtain the desired workability.
- Apply the product smoothly in one coat by brush or roller on the cleaned surfaces.
- Apply adhesives, plaster or cement based renders, making sure that the product is still fresh.
- Clean tools immediately after use with water, otherwise using common solvents (ethyl alcohol, toluene, nitro, etc.) if the product is hardened.

RECOMMENDATIONS

Do not apply on substrates that are not perfectly dry.

Do not apply on surfaces in contact with water or in immersion such as showers, tubs, swimming pools, etc.

Avoid application when temperature is below +5°C or above +35°C.

Protect from frost and excessive heat during storage.

Although the details contained in this product report correspond to the best of our current experience, all the above information must be confirmed after practical applications. Anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of product. The values given in the technical data derived from tests conducted in laboratory, in a controlled environment, so they may be greatly modified by the conditions of installation.

DATI TECNICI

Rev. 06 - 02/2016

Appearance:	Yellow viscous liquid
Composition:	synthetic copolymer in aqueous dispersion and inert
Bulk density	≈ 1,450 Kg/dm ³
pH:	6 - 7
Storage:	12 months in original packaging, protect from frost and excessive heat during storage
Precautions:	Gloves and safety glasses
Hazard classification-:	non dangerous (directive 67/548/EEC)