



la scelta giusta
per grandi progetti.

SCHEDA TECNICA



RM 45

BASIC DETERGENT

PRODUCT

Basic fluid to remove oil, grease and wax.

CHARACTERISTICS

Easy and safe to use, non aggressive liquid.

WHERE TO USE

Removal of traces of oils, fats, waxes, smog deposits, on non-absorbent surfaces.

SUBSTRATES

Ceramics, marble, terrace tiles, natural stone, plastic coatings and concrete.

CONSUMPTION

about 100 - 200 g/sqm according to substrate.

PACKAGING

- 10 kg jerricans on pallet of kg 400;
- 2 kg jerricans on pallet of kg 400.

STORAGE

RM 45 can be store 12 months in its original packaging in a dry place, protected from frost and heat.

ITEM SPECIFICATIONS

The eventual traces' removal of oils, fats and waxes on the non-absorbent surfaces must be made with a specific type of alkaline cleaner such as RM 45 by Edilcol Italia, to be washed with water after 15 minutes since the application.

PREPARATION

- Wear gloves and eye protection.
- Apply with a brush or spray uniformly on the interested surfaces
- Leave the RM 45 for about 15 minutes and then clean with a stiff brush or a domestic mop
- Wash the surface and the used tools thoroughly with water

RECOMMENDATIONS

Always use gloves and eye protection to avoid the contact of the product with skin that, in this case, must be washed with running water.

Do not apply on absorbent surfaces, metals, polished marble.

Do not apply to direct sunlight, on hot surfaces, or with forthcoming rain.

Never pour in unmarked bottles.

Protect from frost and excessive heat during the storage.

Although the details contained in this product report correspond to the best of our current experience, all the above information must be confirmed after practical applications. Anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of product. The values given in the technical data derived from tests conducted in laboratory, in a controlled environment, so they may be greatly modified by the conditions of installation.

DATI TECNICI

Rev. 02 - 02/2016

Appearance:	Transparent liquid	
Composition:	Buffered acid and surfactants	
Bulk density	≈ 1,02 g/cmc	
pH:	≈ 13,0	
Application temperature:	+ 5°C / + 35°C	
Waiting time for rinsing:	≈ 15 minutes	
Storage:	12 months in its original packaging, protect from frost and excessive heat during storage.	
Cautions:	Gloves and eye protection.	
Hazard:	Irritating Decree no. 285/98	(Legislative